

# Himley Ash Grey



**Ibstock**  
At the heart of building



## Product Information

|                        |                  |
|------------------------|------------------|
| Ibstock Code:          | 0358             |
| Type:                  | Wirecut          |
| Facing Description:    | Dragfaced        |
| Dry Brick Weight (kg): | 2kg              |
| Pack Quantity:         | 316              |
| Packaging (standard):  | Banded (plastic) |
| Factory:               | Aldridge         |

## Technical Specification (to BS EN 771-1)

|  |                       |
|--|-----------------------|
| Brick Dimensions (L x W x H mm):           | 215x102x65            |
| Size Tolerances Mean & Range:              | T2 R1                 |
| Configuration:                             | Vertically Perforated |
| Voids (%):                                 | 23-28                 |
| Compressive Strength (N/mm <sup>2</sup> ): | 45                    |
| Active Soluble Salts:                      | S2                    |
| Water Absorption (% weight):               | 12                    |

|   |                  |
|---|------------------|
| Durability:   | F2               |
| Gross Dry Density (Sound Insulation) (Kg/m <sup>3</sup> ):          | 1410             |
| Equivalent Thermal Conductivity "K" value 5% Exposed:               | Refer to Ibstock |
| Initial Rate of Absorption (Suction Rate) (Kg/m <sup>2</sup> /min): | Refer to Ibstock |
| EAN:  | 5036335030875    |

---

11/10/2021